

The '**Mallard**' is a low-profile, multifunction antenna designed for blue-light and amber-light vehicle fleets, combining up to 9 functions within a single panel-mounted unit. With optional fitting kits, the 'Mallard' can be installed using the existing OEM mounting hole, preventing the need to drill additional holes and maintaining OEM functions.

This variant supports **3 Functions** including **2x LTE** and **1x GPS**

### Supplied Coax Extension Cables

| Coax Cables           | 2x LTE        | 1x GPS   |
|-----------------------|---------------|----------|
| Cable Type            | SBC240        | SBC100   |
| length                | 5m or 3m      | 5m or 3m |
| Diameter (mm)         | 6.1           | 2.8      |
| Min. Bend Radius (mm) | 30            | 14       |
| Operating Temp. °C    | -40-80        | -40-80   |
| Termination           | SMA (m)       | SMA (m)  |
| Labeling              | LTE M & LTE A | GPS      |


## Technical Specifications

|                          |                                      |
|--------------------------|--------------------------------------|
| Part No.                 | 7000-313                             |
| Electrical Data          | 2G 3G 4G 5G                          |
| Frequency Range (MHz)    | 698-6000 MHz                         |
| Band                     | 2x2 MiMo 2G 3G 4G 5G                 |
| VSWR                     | <2.1:1 TYPICALLY 1.5:1               |
| Gain                     | Minimum 4dBi                         |
| Isolation                | <-25dB                               |
| Polarisation             | Vertical                             |
| Pattern                  | Omni-directional                     |
| Impedance                | 50Ω                                  |
| Max Power Input (W)      | 10W                                  |
| GPS/GLONASS              |                                      |
| Frequency Range (MHz)    | 1562-1612                            |
| VSWR                     | <2:1                                 |
| Gain                     | 26dB                                 |
| Polarisation             | Right Hand Circular                  |
| Operating Voltage        | 3-5v DC (fed via coax)               |
| Cable                    | 2x 230mm RG316 Terminated to SMA (m) |
| Mechanical Data          |                                      |
| Dimensions (mm)          | H80xW70xL230                         |
| Operating Temp (°C)      | -40 / +80°C (-40° / 176°F)           |
| Material                 | ABS/PC                               |
| Colour                   | Black                                |
| Weight (g)               | 310                                  |
| Ingress Protection       | IP66                                 |
| Cable Data               |                                      |
| Cable Type               | RG316                                |
| length                   | 160mm                                |
| Diameter                 | 2.8                                  |
| Termination              | SMA (f)                              |
| Mounting Data            |                                      |
| Mounting Type            | Panel mount                          |
| Mounting Hole (mm)       | 15mm                                 |
| Max Panel Thickness (mm) | 10mm                                 |


Subject to change without prior notice.

## Supplied Coax Extension Cables


| Coax Cables           | 2x LTE        | 1x GPS   |
|-----------------------|---------------|----------|
| Cable Type            | SBC240        | SBC100   |
| length                | 5m or 3m      | 5m or 3m |
| Diameter (mm)         | 6.1           | 2.8      |
| Min. Bend Radius (mm) | 30            | 14       |
| Operating Temp. °C    | -40-80        | -40-80   |
| Termination           | SMA (m)       | SMA (m)  |
| Labeling              | LTE M & LTE A | GPS      |




## LTE Isolation



## LTE Port Mismatch Efficiency




## LTE Return Loss




## Antenna 3D Gain Plots


820MHz




1820MHz




2140MHz



2600MHz



3600MHz



All graphs & diagrams subject to change without prior notice.

Sure Antennas. 6 Woodway Court, Thursby Rd, Bromborough, Merseyside CH62 3PR, United Kingdom  
Schiphol Airport Tetra, Transpolis Park, Siriusdreef 17-27, 2132 WT Hoofddorp, Netherlands

T. +44 (0)151 363 7377 | E. [sales@sure-antennas.com](mailto:sales@sure-antennas.com)