


SK0200909 'Mallard' 9-in-1 Antenna Black incl. 5m Coax Cables - TETRA

5 YEARS WARRANTY



The '**Mallard**' is a low-profile, multifunction antenna designed for blue-light and amber-light vehicle fleets, combining up to 9 functions within a single panel-mounted unit. With optional fitting kits, the 'Mallard' can be installed using the existing OEM mounting hole, preventing the need to drill additional holes and maintaining OEM functions.

This variant supports **9 Functions** including **TETRA, x4 LTE, x2 LTE and 2x GPS**

Also Available in White: Part No. SK02003919



Part No.	Cable Kit Options
SK0200908	Product Kit : Mallard 9 in 1 Antenna : Black : 4xLTE 2xGPS 2xWiFi 1xTETRA Inc 3m Low Loss Coax Cables - Terminated
SK0200313	Mallard 9 in 1 Black - LTE 2x2 MiMo 5G 4G 3G 2G, 4x4 WiFi 2x GPS & 1x Tetra. Inc 3m Modem Cables

Additional options available upon request.

SK0200909 'Mallard' 9-in-1 Antenna Black incl. 5m Coax Cables - TETRA

Technical Specifications

Part No.		SK0200909		
Electrical Data		TETRA	2G 3G 4G 5G	Wi-Fi
Frequency Range (MHz)	380 - 430 MHz	698-6000 MHz	2.4 GHz & 5.8GHz	
Band	TETRA	4x4 MiMo 2G 3G 4G 5G	2x2 MiMo Dual Band Wi-Fi	
VSWR	<2.1:1 TYPICALLY 1.5:1	<2.1:1 TYPICALLY 1.5:1	<2.1:1 TYPICALLY 1.5:1	
Gain	5dBi	Minimum 4dBi	Minimum 4dBi	
Isolation	-	<-25dB	<-25dB	
Polarisation	Vertical	Vertical	Vertical	
Pattern	Omni-directional	Omni-directional	Omni-directional	
Impedance	50Ω	50Ω	50Ω	
Max Power Input (W)	25W	10W	10W	
GPS/GLONASS				
Frequency Range (MHz)	1562-1612			
VSWR	<2:1			
Gain	26dB			
Polarisation	Right Hand Circular			
Operating Voltage	3-5v DC (fed via coax)			
Cable	2x 230mm RG316 Terminated to SMA (m)			
Mechanical Data				
Dimensions (mm)	H80xW70xL230 *			
Operating Temp (°C)	-40 / +80°C (-40° / 176°F)			
Material	ABS/PC			
Colour	Black			
Weight (g)	310			
Ingress Protection	IP66			
Cable Data				
Cable Type	RG316	RG316	RG316	
length	280mm	160mm	200mm	
Diameter	2.8	2.8	2.8	
Termination	TNC (f)	SMA (f)	SMA (m) Reverse Polarity	
Mounting Data				
Mounting Type	Panel mount			
Mounting Hole (mm)	15mm			
Max Panel Thickness (mm)	10mm			

Subject to change without prior notice. *Excluding external antenna.

SK0200909 'Mallard' 9-in-1 Antenna Black incl. 5m Coax Cables - TETRA

Supplied Coax Extension Cables

Coax Cables	4x LTE	2x Wi-Fi	1x GPS	1x TETRA	1x GPS
Cable Type	SBC240	SBC240	SBC100	SBC195	SBC100
length	5m or 3m	5m or 3m	5m or 3m	5m or 3m	5m or 3m
Diameter (mm)	6.1	6.1	2.8	4.95	2.8
Min. Bend Radius (mm)	30	30	14	25	14
Operating Temp. °C	-40-80	-40-80	-40-80	-40-80	-40-80
Termination	SMA (m)	SMA Reverse Polarity (m)	SMA (m)	BNC (m)	SMA (m) – Motorola and Sepura adaptors supplied.
Labeling	LTE M & LTE A	Wi-Fi M & Wi-Fi A	GPS	TETRA	GPS TETRA


A brand of




www.sure-antennas.com




LTE Isolation




LTE Port Mismatch Efficiency




LTE Return Loss




LTE to Wi-Fi Port Isolation




TETRA to LTE/Wi-Fi Isolation




TETRA Port Mismatch Efficiency




TETRA Port Return Loss




Wi-Fi Port Isolation



Wi-Fi Port Mismatch Efficiency




Wi-Fi Port Return Loss




SK0200909 'Mallard' 9-in-1 Antenna Black incl. 5m Coax Cables - TETRA

Antenna 3D Gain Plots


820MHz




1820MHz




2140MHz



2600MHz



3600MHz



All graphs & diagrams subject to change without prior notice.

Sure Antennas. 6 Woodway Court, Thursby Rd, Bromborough, Merseyside CH62 3PR, United Kingdom
Schiphol Airport Tetra, Transpolis Park, Siriusdreef 17-27, 2132 WT Hoofddorp, Netherlands

T. +44 (0)151 363 7377 | E. sales@sure-antennas.com

A brand of



www.sure-antennas.com