

SM3400W50S0-4 SM3400 Transmitter/ Divider Unit



The **SM3400 'divider unit'** was specifically designed to enable **two transmitters to transmit simultaneously**, without the use of switching circuitry. The passive unit can operate **380-430MHz**. With an **insertion loss of less than -0.4dB*** and isolation port to port of **less than -30dB across 50MHz bandwidth** this unit offers a great performance against active switch units. This unit can be custom built to **support frequencies within 70MHz to 2.4GHz**. Please contact us for more options.

Technical Specifications

Part No.	SM3400W50S0-4	SM3400W25S0-4	SM3400W10S0-4
Frequency Range (MHz)	380 - 430MHz		
Band	TETRA x 2		
Impedance	50Ω		
Max Power Input	Whip 50W Internal Elements	Whip 25W Internal Elements	Whip 10W Internal Elements
Insertion Loss	<0.4dB*		
VSWR	<1.2:1		
Port Isolation	>30dB		
Connection	SMA (f)**		
Operating Temp. (°C)	-20°C to +60°		

*Excluding combining losses. **Custom Connection Configurations available.

Subject to change.

Sure Antennas. 6 Woodway Court, Thursby Rd, Bromborough, Merseyside CH62 3PR, United Kingdom
Schiphol Airport Tetra - Siriusdreef 17-27, Transpolis Park, 2132 WT Hoofddorp, Netherlands

T. +44 (0) 151 363 7377 | E. sales@sure-antennas.com

www.sure-antennas.com

A brand of

